Technical Data Sheet

Beverage Stabilization

L(+) Tartaric Acid

L(+) Tartaric Acid stabilizer is a fruit acid found in nature. It possesses a high degree of purity and has been specially selected for application in the beverage industry.

The specific advantages of L(+) Tartaric Acid stabilizer:

- High degree of product purity
- For targeted acid enrichment in basic champagne wines 1,25 lb/100 gal (150 g/hl) in Germany; (please observe the legislation in the relevant country)
- For acid harmonization in the production of beverages on a fruit or vegetable basis (please observe the legislation in the relevant country)

Application

L(+) Tartaric Acid stabilizer should be added to the basic champagne wine after the cuvee composition, in order to avoid exceeding the maximum permitted quantity in the finished champagne. The same applies to the application in the fruit beverages sector, the addition should first take place after the composition of the recipe.

L(+) Tartaric Acid stabilizer is dissolved free of lumps in 10-20 times the volume of beverage and slowly added to the entire beverage by intensive mixing. After addition, continue mixing for some minutes to ensure even distribution.

Safety

If L(+) Tartaric Acid stabilizer is used correctly, there are no known detrimental effects.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

Storage

L(+) Tartaric Acid stabilizer should be stored cool and dry. Open packages should be immediately reclosed tightly and quickly used up.

Delivery Information

L(+) Tartaric Acid stabilizer is sold under article no. 64.206 and is available in the following package sizes:

2.2 lb (1 kg) PE foil

25 x 2.2 lb (1 kg) in cardboard box

L(+) Tartaric Acid stabilizer is sold under article no. HW.001 and is available in the following package size:

55.1 lb (25 kg) paper bag

Certified Quality

L(+) Tartaric Acid stabilizer is monitored regularly during the production process to ensure consistently high quality. These inspections cover technical function criteria as well as compliance with the law governing the production and sale of foodstuffs. Strict controls are also carried out immediately before and during final packing.



North America 44 Apple Street Tinton Falls, NJ 07724 Toll Free: 800 656-3344 (North America only) Tel: +1 732 212-4700

Europe/Africa/Middle East Auf der Heide 2 53947 Nettersheim, Germany Tel: +49 2486 809-0

Friedensstraße 41 68804 Altlußheim, Germany Tel: +49 6205 2094-0

55450 Langenlonsheim, Germany Tel: +49 6704 204-0

No. 3, Lane 280, Linhong Road Changning District, 200335 Shanghai, P.R. China Tel: +86 21 5200-0099

Singapore

4 Loyang Lane #04-01/02 Singapore 508914 Tel: +65 6825-1668

Rua Clark, 2061 - Macuco 13279-400 - Valinhos, Brazil Tel: +55 11 3616-8400

For more information, please email us at filtration@eaton.com or visit www.eaton.com/filtration

© 2016 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete. since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.



EN 1 B 5.6.2 12-2016