

Pure Fermentation LALVIN® 2323 YSEO

Saccharomyces Cerevisiae

LALVIN 2323 YSEO yeast is a specially selected dry active yeast, which is particularly beneficial for the fermentation of red wine must and red wine mash. The special advantages are color extraction, production of aroma that reminds of figs and dats. A rapid main fermentation and high-end fermentation rate are further advantages of the yeast strain.

The YSEO production process helps to reduce the production of sulfur compounds especially during the fermentation of extreme different grape qualities.

LALVIN 2323 YSEO yeast is particularly suitable for voluminous red wines with southern French style (Cabernet Sauvignon, Cabernet Franc, Pinot Noir).

The specific advantages of LALVIN 2323 YSEO yeast:

- High nutrient requirements
- Good temperature and alcohol tolerance
- Quickly displaces wild yeasts and bacteria thanks to "killer characteristics"
- Rapid start of fermentation and main fermentation
- Low formation of undesirable fermentation by-products

Application

As a basic rule, musts should be inoculated with LALVIN 2323 YSEO yeast as early as possible. Longer maceration time favors uncontrolled multiplication of wild yeasts and undesirable bacteria. Fermentation problems are reliably prevented with the dosage indicated in the table.

The quantities stated are guide values. They should be adapted to the individual requirements depending on the health of the grapes, the temperature, and the batch size etc. For large batches, adequate cooling must be ensured.

LALVIN 2323 YSEO yeast is best stirred into a 10:1 must/water mixture at 95 – 104 °F (35 – 40 °C), stirred again after approximately 20 minutes and added to the must.

Application	Quantity required lb/1,000 gal (g/hl) under	
	normal fermentation	difficult conditions
Red wine mash	1.6 – 2.5 (20 – 30)	2.5 – 3.3 (30 – 40)
Red wine must	1.6 – 2.1 (20 – 25)	2.5 – 2.9 (30 – 35)

The optimum fermentation temperature is between 71.6 – 82.4 °F (22 – 28 °C). The minimum starting temperature is 64.4 °F (18 °C). LALVIN 2323 YSEO yeast should only be added to heated must or mash after recooling or rather cooling to 68 °F (20 °C).

The addition of 0.005 lb SIHA® Vitamin B₁ yeast nutrient per 1,000 gal of must (600 mg per 1,000 l) creates even better multiplication, fermentation and metabolism conditions. For final fermentation of stuck wines, we recommend adding an additional dose of 2.5 lb /1,000 gal (30 g/hl) SIHA PROFERM™ Plus combined yeast nutrient.

Under these conditions it is beneficial to accustom the yeast to the fermentation conditions. This is best achieved by adding the quantity of yeast required for the total quantity of wine to approximately 10% of the total product to be fermented and fermenting until approximately half the sugar present is used up. This mixture is then added to the remaining 90% of the wine for final fermentation. Yeasts adapted in this way usually start fermenting more quickly and have a lower tendency to die off than if they are added directly to the total quantity.

Product Characteristics

Selection over several years enabled us to reduce the color adsorption of the yeast and therefore to achieve better color yield. This very positive yeast quality is continuously reinforced and secured through further selection. Due to increased polysaccharide formation, wines fermented with LALVIN 2323 YSEO yeast are particularly harmonious and aromatic with high "mouthfeel".

LALVIN 2323 YSEO yeast shows an advantageous fermentation curve with high final degree of fermentation. Wild yeasts and undesirable bacteria are suppressed. LALVIN 2323 YSEO yeast generates no undesirable fermentation by-products such as SO₂, H₂S, acetaldehyde, pyruvate, α-ketoglutaric acid, volatile acid, or ester.

LALVIN 2323 YSEO yeast can produce up to 15% alcohol by volume. The practical alcohol yield is approximately 47% of the sugar content. For each lb (kg) of sugar fermented, approx. 247 kJ (546 kJ)/59 kcal (130 kcal) of heat is released.

Safety

No safety information has to be provided for LALVIN 2323 YSEO yeast, since the product is used directly for food production. There are no known risks to humans or the environment during storage, handling and transport of the product.

Storage

LALVIN 2323 YSEO yeast is packed in airtight multi-layer aluminum film in an inert gas atmosphere. The integrity of the vacuum pack is easy to monitor.

In undamaged packaging, LALVIN 2323 YSEO yeast can be stored for four years at 39 to 50 °F (4 – 10 °C). Short-term storage at 68 °F (20 °C) is acceptable.

Once a package has been opened, it should be used up as soon as possible.

Delivery Information

LALVIN 2323 YSEO yeast is sold under article no. 93.324 and is available in the following package sizes:

1.1 lb (500 g)	aluminum sandwich foil block pack
20 x 1.1 lb (500 g)	aluminum sandwich foil block pack in carton

Certified Quality

During the production process, LALVIN 2323 YSEO yeast is continuously monitored to ensure consistently high quality.

These inspections cover technical function criteria as well as conformance with the relevant laws governing the production and sale of foodstuffs. Strict controls are carried out immediately before as well as during final packaging.

LALVIN 2323 YSEO yeast conforms to the purity regulations of the International OIV Code for wine treatment products and to the regulations of the German Wine Ordinance. Please pay attention to the national laws.

LALVIN® is a registered trademark of Lallemand Inc.

North America

44 Apple Street
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America only)
Tel: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0

Friedensstraße 41
68804 Altlufzheim, Germany
Tel: +49 6205 2094-0

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

China

No. 3, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 5200-0099

Singapore

4 Loyang Lane #04-01/02
Singapore 508914
Tel: +65 6825-1668

Brazil

Rua Clark, 2061 - Macuco
13279-400 - Valinhos, Brazil
Tel: +55 11 3616-8400

**For more information, please
email us at filtration@eaton.com
or visit www.eaton.com/filtration**

EN
1 B 2.2.44
12-2016



Powering Business Worldwide

© 2016 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.